Serial No. 10/605,693 Docket No. 27475/06642

Page 2 of 4

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in this

application:

1. - 19. (Canceled).

20. (Currently amended) A method of changing the combination of a lock, said

method comprising:

inserting a key into a key cylinder of the lock;

rotating said key, such that said key cylinder is rotated from a first position to a second

position;

rotating a user graspable number dial relative to a user graspable tumbler dial; and

turning the key and the key cylinder back to first position;

The method set forth in claim 19 wherein the step of rotating the key further comprises

decoupling the number dial from the tumbler dial.

21. (Currently amended) The method set forth in claim 19–20 wherein the key

cylinder is mounted in the tumbler dial at a position offset from the rotational center of the

tumbler dial.

22. (Currently amended) The method set forth in claim 19-20 wherein at least ten

combination changes are available.

23. (Currently amended) The method as set forth in claim 19-20 further comprising

the step of aligning a marking with a number on said number dial, wherein said number

correlates to a combination to unlock the lock.

24. - 31. (Canceled).

{00043765.DOC;1}

2

Serial No. 10/605,693 Docket No. 27475/06642 Page 3 of 4

32. (Currently amended) The method set forth in claim 19–20, wherein the lock remains locked while the combination is changed.